

Article no.	Description
8117171-003	Vensterdoos Topbox 6P (clic clac) BV 170x170x50 mm blanco+lak FSC®
8100000-054	Vensterdoos Topbox 6P (clic clac) BV 250x250x50mm blanco met lak
8100000-055	Vensterdoos Topbox 6P (clic clac) BV 270x270x50mm blanco met lak FSC®
8100000-056	Vensterdoos Topbox 6P (clic-clac) BV 170x170x80 mm blanco met lak FSC®
8111000-008	Bonbondozen 250 gram wit 112x61x55 mm
8111000-009	Bonbondozen 375 grs. 121x69x60mm blanco lak
8111000-014	Bonbondozen 750 grs 150x85x86 mm blanco lak
8111000-020	Bonbondozen 500 gram 132x76x70 mm blanco met lak
8111000-025	Bonbondozen 125 grs. 78x58x45mm blanco lak
8111000-026	Bonbondozen 1000 grs. 163x97x82mm wit + lak
8111000-034	Bonbondozen 2pr 65x37x33 mm wit + lak

28-01-2025

Declaration of Compliance

This product complies with the following legal requirements or recommendations:

- EU-Framework Regulation on materials and articles intended for food contact: (EC) No. 1935/2004
- Regulation (EU) No. 10/2011 and amendments to date
- Regulation (EU) No. 2023/2006
- German LFGB §§ 30 and 31
- Dutch Commodities Act
- European Guideline 94/62/EC concerning heavy metal content in packaging and packaging waste

Determination of conformity:

In the plastic regulation (EU) No. 10/2011, the following overall migration limits (OML) are defined:

- 10 mg / dm² coming into contact with the food surface
- 60 mg / kg food or food simulant (provided with materials in contact with food for infants and young children)
- For all test results the standard EU factor of 6dm² /1kg is applied

Conditions of use:

We confirm with this declaration that the above article fulfils the statutory provisions for the contact with the following food fillings: drinks, confectionery, fruit and vegetables, fats and oils, animal products, dairy products, dry food mixes with and without fat. We further confirm that no PCR is used (post-consumer recycled material).

Results of the Overall Migration (OML):

Type of Analysis	Reference Standard	Reference Substance	Duration	Result
OM2**	EU10/2011	A - Ethanol 10%	10 days/40°C	< 10 mg/dm ²
OM2	EU10/2011	B - Acetic Acid 3%	10 days/40°C	< 10 mg/dm ²
OM2**	EU10/2011	D2 – Vegetable Oil	10 days/40°C	< 10 mg/dm ²
OM2	EN 14338	E - Tenax	10 days/40°C	< 1 mg/dm ²

** For HDPE films, high temperature applications are possible with the exemption of acidic foods as simulated under OM5 – 2 hrs/100°C.

Information on substances with restrictions (SML) and / or dual-use specifications:

During manufacturing of the granules, which are used for our products, substances with restrictions (SML) and / or dual-use additives are used. We confirm compliance with the limits for the specified types of food and application conditions. According to the information from our raw material suppliers, the substances specified in the table below may be included. The limit values given in brackets are not exceeded in our film formulations. All transparent foils blunt or with slip agents as well as the blue colors typical for the food processing industry are taken into account. For other colors or special technical additives, additional substances with restrictions may arise. The migration limit of these substances are also adhered to in any case. Please contact your account manager for more information.

Non-intentionally added substances (NIAS):

Foils made from polyethylene can contain NIAS. We monitor this closely in collaboration with our accredited laboratory. NIAS are identified and evaluated based on a 10 ppb screening with simulation substance Ethanol 95 Vol.-%, 10 days / 60°C, resulting in measurements by means of GC/MS-FID. We can conclude that our foils comply with European regulation on these substances.

SML	Dual-Use
FCM 132 Vinylidene fluoride (5mg)	E170 / FCM 21 carbonic acid, salts
FCM 264 1-octene (15mg)	E171 / FCM 610 titanium dioxide
FCM 282 Hexafluoropropylene (1mg)	E172 / Eisenoxid
FCM 356 1-Hex (3mg)	E296 / FCM 499 malic acid
FCM 433 Antioxidant (6mg)	E470a / FCM 9 acids, C2-C24, aliphatic, linear, monocarboxylic from natural oils and fats
FCM 483 n-octylphosphonic acid (0,05mg)	E470a / Calcium stearate
FCM 974 Phosphorous acis, mixed (10mg)	FCM 616 quartz
Ref No Annex II - Aluminium (1mg)	E551 / FCM 504 silicon dioxide,
Ref No Annex II - Antimony (0.041mg)	E570 / FCM 106 Sterainesaure
Ref No Annex II - Barium (1mg)	E553b / FCM 615 Talc
Ref No Annex II - Nickel (0.02mg)	E900 / FCM 575 / Polydimethylsiloxan
Ref No Annex II - Iron (48mg)	
Ref No Annex II - Zinc (5mg)	
Ref No Annex II - Copper (5mg)	

**Microbiological Analysis:**

Testing reference: DIN 54378

Aerobic mesophilic count:	<1 CFU/100cm ²
Yeast and moulds:	<1 CFU/100cm ²
Enterobacteria:	<1 CFU/100cm ²

Further declarations:

- **Heavy metal:** The cumulative amount of heavy metals lead (Pb), mercury (Hg), Cadmium (Cd) and chromium VI (Cr^{VI}) in the materials supplied does not exceed the limited 100 ppm, which compliance with EC Directive 94/62/EC on packaging and Packaging Waste.
- **REACH:** The above mentioned items and all components of the packaging we deliver do not contain any substances (SVHC) from the current candidate list. In case of expansion of the candidate list, we are obliged to inform our customer immediately as soon as our products/packaging do contain one of the new mentioned substances with more than 0.1%.
- **MOSH/MOAH:** Cardboard types based on recycled fibers or food contact materials may contain mineral oils, including MOSH and MOAH. European legislation has stated that these mineral oils must be below a certain migration limit. Dimensio Verpakkingen BV complies with the guidelines and limits regarding the migration of mineral oils.

Conclusion:

In terms of EU-framework Directive (EC) No. 1935/2004 and §§ 30 and 31 LFGB, published in the Bundesgesetzblatt (Federal Law Gazette) No 55 of 6.09.2005 there are no objections against the use of the product for the manufacture of articles intended for food contact.

This declaration is valid for the product delivered by us as specified above in the condition EXW of the production plant. Dimensio Verpakkingen BV cannot be held liable for any modification or further processing. Traceability is guaranteed through our batch number. The Regulation (EU) No. 10/2011 provides guidelines for the selection of test conditions to be used for various food products. According to that and under consideration of the food contact conditions stated, the product complies with the stipulations of these Regulations regarding the packaging of food products to be packed. The user shall verify himself that the product is suitable for the intended food to be packed beyond the stipulations of the Directives. In particular, it is emphasized that in case of printed material, no contact is allowed between the printing ink and the food product.

Notes on storage:

In order not to adversely affect technical properties we recommend the following storage conditions:

- Protect from direct sunlight (UV)
- Dry storage at temperatures between 5°C to 30°C
- Opened merchandise, pack again carefully

Technical properties decrease with increasing temperature. Therefore, this product should be used in a temperature range of max. -25°C to +75°C.

A handwritten signature in black ink, appearing to read 'Younes Ackermann'.

Younes Ackermann
Kwaliteitscoördinator
Dimensio Verpakkingen BV
Quality Assurance
kwaliteit@dimensio.nl